

Honeycomb Kraft Paper

Interior only



Specifications	Description
Thickness	1-3/8" (34.93 mm), 1-3/4" (44.45 mm)
Size	48" x 120" (1219 mm x 3048 mm). Others on request.
Core	Honeycomb Kraft Paper
Fire Rating	NFR
Stiles	1 1/2" (38 mm) of low density wood.
Rails	1 1/2" (38 mm) of low density wood.
Faces	MDF, Plywood (choice of species, 2 ply only), Wood Veneer, Plastic Laminate (Bonded to rigid crossband). Available NAUF.
Finish	Primer only, Painted, Painted Veneer, Stained Veneer, Clear Coat Veneer. The top and bottom are sealed.
Adhesive	Type 1, fully weatherproof; PVA polyvinyl acetate (NAUF); VOC < 14.98 g/L.
Standard	ANSI/WDMA I.S. 1 A-2013 ; CAN/CSA 0132.2 Series-90(R1998) AWI/AWMAC WI 2nd Edition, 01 October, 2014
Door Weight	For 1 3/8" (34.93 mm) - 1.3 lbs/sf For 1 3/4" (44.45 mm) - 1.7 lbs/sf
Warranty	Covered by a limited warranty of 2 year against manufacturing defects. (No exterior warranty). Please contact us for more details.
Crossbands	One Piece High Density Fiberboard (HDF)
Options	Bifolds, sliding, swivel, retractable (pocket doors) doors. Prehung doors Doors with low VOC primer Machining on request. Consult our machining charter Stiles and rails with primer or sealed individual identification (tag)
Note	The stiles and rails dimensions are untrimmed. These dimensions will vary according to the fit of the finished dimensions. For more information, consult the Technical Data Chart.

TECHNICAL SPECIFICATIONS