



# Honeycomb Kraft Paper

Interior only

Specifications	Description
<b>Thickness</b>	1-3/8" (34.93 mm), 1-3/4" (44.45 mm)
<b>Size</b>	36" x 96" (914 mm x 2438 mm)
<b>Core</b>	Honeycomb Kraft Paper
<b>Fire Rating</b>	NFR
<b>Stiles</b>	1 1/2" (38 mm) of low density wood.
<b>Rails</b>	1 1/2" (38 mm) of low density wood.
<b>Faces</b>	Hardboard Molded Panel. Available NAUF.
<b>Finish</b>	Primer only or painted in the factory. The top and bottom are sealed. Custom color development.
<b>Adhesive</b>	Type 1, fully weatherproof; PVA polyvinyl acetate (NAUF); VOC < 14.98 g/L.
<b>Standard</b>	ANSI/WDMA I.S. 1 A-2013 ; CAN/CSA 0132.2 Series-90(R1998) AWI/AWMAC WI 2nd Edition, 01 October, 2014
<b>Door Weight</b>	For 1 3/8" (34.93 mm) - 1.3 lbs/sf For 1 3/4" (44.45 mm) - 1.7 lbs/sf
<b>Warranty</b>	Covered by a limited warranty of 2 year against manufacturing defects. (No exterior warranty). Please contact us for more details.
<b>Options</b>	Bifolds, sliding, swivel, retractable (pocket doors) doors. Prehung doors Doors with low VOC primer Machining on request. Consult our machining charter Stiles and rails with primer or sealed Individual identification (tag)
<b>Note</b>	The stiles and rails dimensions are untrimmed. These dimensions will vary according to the fit of the finished dimensions. For more information, consult the Technical Data Chart.

TECHNICAL SPECIFICATIONS