



Particleboard

Interior only

Specifications	Description
Thickness	1-3/4" (44.45 mm)
Size	36" x 96" (914 mm x 2438 mm)
Core	Particleboard, medium density of 28-32 pounds per foot cube. Conforms to the standard CSA-0188 and standard ANSI A208-1. (LD-1/LD-2). Available NAUF/FSC.
Fire Rating	NFR, 20 Minutes
Stiles	1 1/2" (38 mm) of low density wood.
Rails	1 1/2" (38 mm) of low density wood.
Faces	Hardboard Molded Panel. Available NAUF.
Finish	Primer only or painted in the factory. The top and bottom are sealed. Custom color development.
Adhesive	Type 1, fully weatherproof; PVA polyvinyl acetate (NAUF); VOC < 14.98 g/L.
Standard	ANSI/WDMA I.S. 1 A-2013 ; CAN/CSA 0132.2 Series-90(R1998) AWI/AWMAC WI 2nd Edition, 01 October, 2014 Available UL Standards :- <ul style="list-style-type: none"> · UL 10B - Standard for Fire Tests of Door Assemblies · UL 10C - Standard for Positive Pressure Fire Tests of Door Assemblies · CAN/ULC S104 Standard Method for Fire Tests of Door Assemblies (Canada) · UL 1784 Standard for Air Leakage Tests of Door Assemblies and Other Opening Protectives
Door Weight	1 3/4" (44.45 mm) - 5.5 lbs/sf
Warranty	Covered by a limited warranty of 2 year against manufacturing defects. (No exterior warranty). Please contact us for more details.
Options	Bifolds, sliding, swivel, retractable (pocket doors) doors. Prehung doors. Doors with low VOC primer Machining on request. Consult our machining charter Stiles and rails with primer or sealed Individual identification (tag)
Note	The stiles and rails dimensions are untrimmed. These dimensions will vary according to the fit of the finished dimensions. For more information, consult the Technical Data Chart.

TECHNICAL SPECIFICATIONS