

Stile and Rail Solid Lumber Core

Exterior only

Spec	ifications	Description
TECHNICAL SPECIFICATIONS	Door Styles (Panel Styles may vary based on required construction)	French, Traditional, Archtop (radius), Other
	Panel Design (Panel Styles may vary based on required construction)	Square-top, Archtop (radius) panels, Eyebrow, Provence, Other
	Thickness	1-3/4" (44.45 mm) , 2-1/4" (57.15 mm)
	Size	60" x 144" (1524 mm x 3657.6 mm)
	Default Face Dimensions	Stiles: 5-1/2" (139.7 mm) Top Rail: 5-1/2" (139.7 mm) Bottom Rail: 10" (254 mm) (minimum 12" (304.8 mm) for over 36" (914.4 mm) wide) Lock Rail: 6-1/2" (165.1 mm) Muntins (Simulated Divided Lite) & Bars (True Divided Lite): 1-3/8" (34.93 mm) (including glass stops) Crossrail (Intermediate): 3-5/8" (92 mm) Mullions: 3-5/8" (92 mm)
	Fire Rating	NFR
	Surface Material	Primer Only Painted : Stiles and Rails - Mahogany, Panels MDF Wood Veneer : Standard 1/16" (1.58 mm) Standard 1/8"; Mahogany, Cherry, Walnut, Pine, Fir, White Oak. Expansive veneer oferings available.
	Joinery	Cope & Stick : Doweled
	Core and Panel Material	Stiles: SCLC Top Rail: Solid Lumber Bottom Rail: Solid Lumber Lock Rail: Solid Lumber Mid-rails: Solid Lumber Mullions: Solid Lumber Louvers (Standard, False, Chevron): Solid Lumber (no warranty Raised Panel: MDF Flat Panel: MDF Paint Grade Panel / False Louvers: Solid Wood
	Panel Options	Raised Panel: 1-5/8" Veneer Wrapped Raised Panel: N/A Flat Panel: 5/8" V-Groove Flat Panel: 1-1/8" V-Groove Raised Panel: 1-5/8"
	Sticking Options	Ogee, Ovolo, No profile, Square, Quarter Round, Custom options available
	Raised and Applied Moulding	Available upon request
	Glass	Standard Glass (Maximum cutout): -1/4" Tempered -5/8" Tempered insulated Optional Glass Types: -Tempered: Clear, Clear Bevel, Acid Etched, Acid Etched with Clear Bevel -Laminated: Clear, White Additional Options: Insulated Glass, Low E and Argon
	Machining (Typical factory machining)	All custom hardware preparations
	Warranty	5 Year Warranty (must be factory fnished)